



PRODUCT LEAFLET

TECHNICAL SPECS

APPLICATION NOTE

S-VIT – the ruggedized, compact high speed camera for automotive safety testing and harsh industrial as well as research applications. More light sensitive than ever.

Applications

The S-VIT is particularly suited for all applications where a compact and portable yet robust camera is essential:

- Automotive safety testing – on-board full size crash vehicle or sled body structures where the camera is fitted into tight areas like door panels or the pedal area
- Industrial or military applications with Hi-G shocks and limited space – like excenter presses and similar devices

Why the S-VIT?

- Perfectly balanced performance – 1,250 fps @ 800 x 600 provides you with excellent image quality and a frame rate suitable for a wide range of automotive test applications
- Robust design – designed for many years of rough handling in HiG-applications (milled aluminum)
- Simple to use – the camera control software is easy to use, even for novices and occasional users; operator training is not necessary – yet provides full control of the camera settings and functions

Unique features

- **Simple and easy to integrate** – due to its built-in PowerPC, the S-VIT can duplicate the control- and status lines of a film camera. This plus the range of available connectors make the integration into a given environment, i.e. by replacing an older film-based camera, a cinch. Modifications on the aircraft as well as on the test routine are kept to a minimum.
- **High Sensitivity** – the S-VIT offers a light sensitivity greater than in previous cameras models. In many applications and settings, the camera delivers well-lit images without extra illumination, while in others only minimal extra light is necessary.
- **Modular concept** – you don't have to buy an off-the-shelf product which might or might not suit your application. Have your S-VIT configured for a perfect match by choosing from an extensive range of extension.
- **Selectable ROI** – the customer can select the most suitable image format (ROI, region of interest) almost without limitations, for best camera performance and image quality



Car crash (on board)



Car crash (off board)


Your local AOS partner:

Specifications are subject to change without prior notice – v08.2012



AOS Technologies AG, Taefernstrasse 20,
CH-5405 Baden-Daettwil
Tel. +41 (56) 483 3488, Fax + 41 (56) 483 3489
info@aostechnologies.com
www.aostechnologies.com

Technical key specifications

| | |
|--|--|
| Image Sensor | Progressive CMOS, 1280 x 1024 pixels, mono or color |
| Sensor size (@ full resolution) | 17.82 x 14.33 mm, 14 µm pixel size |
| Light sensitivity | ISO 3200 (monochrome), ISO 1600 (color) |
| Dynamic range | 5-, 8- or 10 bit, adjustable by user |
| Gain control | User selectable, High Dynamic Range (HDR) mode |
| Frame rate at full resolution | 500 fps @ 1280 x 1024 pixels |
| Typical fps/resolution settings | 1280 x 1024 @ up to 500fps 900 x 700 @ up to 1'000fps 800 x 600 @ up to 1'250fps |
| Max. frame rate | 100'000 fps |
| Shutter type | Global electronic shutter |
| Shutter exposure times | 4 µsec to 1/frame rate |
| Image memory | Built-in DRAM, circular buffer |
| Sequence length | 2.2 sec @ 800 x 600 / 1250fps (1.3 GB memory) 4.4 sec @ 800 x 600 / 1250fps (2.6 GB memory) 8.8 sec @ 800 x 600 / 1250fps (5.2 GB memory) 17.6 sec @ 800 x 600 / 1250fps (10.4 GB memory) |
| Data Interface | Gigabit Ethernet (1'000 Mb/s) RJ45, other connectors on request |
| Frame synchronisation | Sync in, Sync out (TTL) |
| Multi-camera operation | Yes |
| Memory Interface | Built-in CF interface (optional), accepting CF cards for non-volatile data storage |
| Power supply | 12 VDC (9...16VDC), other voltage ratings on request |
| Power consumption | 14 W (w/o data link), 18 W (with data link) |
| Battery | Built-in, rechargeable NiMH battery allowing 3 hours camera operation. |
| Video Interface (optional) | SDI (digital) or PAL/NTSC (analog) |
| Operating temperature | 0 ... +45 °C (32 ... 113 °F) |
| Storage temperature | -40 ... +70 °C (-40 ... 158 °F) |
| Shock resistance | 100G for 15msec, 3 axis , up to 200G during short peaks |
| Size, weight (standard model) | 71 x 71 x 122 mm, 1100 gr |
| I/O Connector | <p>LEMO Type: FGG.2B.314.CLAD82Z ODU Type: S22LOC-P14MFG0-8200</p>  |
| CE | In compliance with relevant standards |

different pinout configuration and connectors on request